

Product Description

The KBC ESSGS2-G1-B is an Industrial Unmanaged Gigabit Plus Switch designed for critical, space-constrained, and harsh-environment applications. Part of KBC's next-generation Unmanaged Plus family, the ESSGS2-G1-B provides the plug-and-play simplicity of an unmanaged switch while adding **PowerPilot™ PoE Control**—a lightweight web-based GUI that enables users to check PoE usage and requested PoE power, power-cycle, and schedule PoE ports without requiring any advanced network configuration.

Built in a compact IP40 metal enclosure with extended operating temperatures and industrial-grade EMC protection, the switch is engineered for reliable operation in transportation, utilities, energy, perimeter security, industrial automation, and remote infrastructure deployments.


PowerPilot



Product Features

- Unmanaged design with PowerPilot™ PoE control
- Web-based GUI interface
- PoE power monitoring per port
- PoE port on/off control
- PoE power scheduling (daily/weekly)
- Auto Sensing/self-reset PoE function
- PoE budget display
- 3x 10/100/1000Base-T(x) ports; 2 PoE+ ports and 1x Non-PoE Port
- Each PoE port outputs up to 30W; 60W total PoE budget
- Supports IEEE802.3af&at
- Overload current protection and reverse polarity protection
- Level 3 ESD protection
- Rugged IP40 housing design
- Supports DIN-rail or wall-mount
- Unique DIN mount design makes mounting and removal easy

Typical System Configuration



Specifications

Standards

IEEE Standards	IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3z IEEE802.3ab, IEEE802.3af&at
----------------	---

Ports

10/100/1000Base-T	RJ45 (3, 2 with PoE/PoE+)
-------------------	---------------------------

Switch Performance

Architecture	Store-and-forward
Memory Buffer	512K
Switch Capacity	10Gbps
Mac Table	1K

PoE

Standard	IEEE802.3af/at
PSE Type	End-span
Power Pin Assignment	1/2(+), 3/6(-)
PoE Power Output	Each PoE port up to 30W

Power ⁽¹⁾

Redundant Power Input	45 ~ 57Vdc
Power Consumption	< 5W (without PoE)
PoE Budget	60W max.
Overload Current Protection	Yes
Reverse polarity protection	Yes

Protection


Surge	6KV, IEC61000-4-5
ESD	ESD Level 4: IEC61000-4-2 RS Level 3: IEC61000-4-3 EFT Level 4: IEC61000-4-4 CS Level 3: IEC61000-4-6

Environmental

Operating Temperature	-40°C ~ +75°C
Storage Temperature	-40°C ~ +85°C
Operating Humidity	5% to 95% non-condensing

Mechanical

Enclosure	IP40
Dimension (L×W×H)	62mm × 103mm × 100mm
Weight	0.6kg



Order Information

ESSGS2-G1-B: Industrial Unmanaged Ethernet Gigabit Switch with PowerPilot™ PoE Control, 3x10/100/1000Base-T(x) ports, 2 PoE+ Ports

1. Power supply sold separately. See www.kbcnetworks.com for more information.

Due to ongoing technological improvements, product specifications are subject to change without notice. KBC is not liable for any errors, omissions or changes of any description of the goods contained herein. This information is for the sole purpose of identifying the products and KBC makes no warranty that the products conform to any description contained herein. Do not rely solely on any representations, statements, or assertions concerning these Products contained herein.